

IN THE CLAIMS

Please enter the following amendments. The amendments are fully supported in the specification and no new material is added.

1. (Currently Amended) A ~~low-impedance~~ band-gap reference circuit, comprising:
 - a band-gap reference unit circuit;
 - a buffer circuit electronically coupled with said band-gap reference unit circuit; and
 - a voltage pull-up device electronically coupled ~~with~~ between said band-gap reference unit circuit and said buffer circuit, wherein said voltage pull-up device acts to reduce a required supply voltage to maintain a band-gap reference voltage and wherein said voltage pull-up device is implemented as a transistor with a VBE of less than 1.0 volts.
2. (Currently Amended) A ~~low-impedance~~ band-gap reference circuit as described in Claim 1, wherein said band-gap reference circuit resides in an integrated circuit device.
3. (Currently Amended) A ~~low-impedance~~ band-gap reference circuit as described in Claim 1, wherein said band-gap reference circuit is implemented in a silicon substrate.
4. (Currently Amended) A ~~low-impedance~~ band-gap reference circuit as described in Claim 1, wherein said buffer circuit is implemented as a transistor.
5. (Cancelled)
6. (Currently Amended) A ~~low-impedance~~ band-gap reference circuit as described in Claim 1, wherein said band gap reference voltage is provided by current through a transistor with a VBE of less than 1.0 volts.
7. (Currently Amended) An electronic device, comprising:
 - a silicon substrate;
 - electronic circuitry constructed in said silicon substrate; and
 - a ~~low-impedance~~ band-gap reference circuit comprising a band gap reference unit, a buffer circuit, and a voltage pull-up device electronically coupled in said electronic device, wherein said electronic circuitry requires reference to the output voltage of said band-gap reference circuit and said band-gap reference circuit is enabled for low impedance by said a

buffer circuit, wherein said buffer circuit comprises comprising a transistor with a VBE of less than 1.0 volts, and wherein said voltage pull-up device is coupled between said band-gap reference unit and said buffer circuit.

8. (Original) An electronic device as described in Claim 7, wherein said electronic device is an integrated circuit device.

9. (Cancelled)

10. (Cancelled)

11. (Currently Amended) An electronic device as described in Claim 7, wherein said transistor with a VBE of less than 1.0 volts ~~less than 1.0 Vbe~~ is connected as an emitter follower.

12. (Original) An electronic device as described in Claim 7, wherein said band-gap reference circuit is enabled for low supply voltage.

13. An electronic device as described in Claim 12, wherein said band-gap reference circuit is enabled for said low supply voltage by a voltage pull-up device.

14. (Cancelled)

15. (Previously Presented) An electronic device as described in Claim 13, wherein said band gap reference voltage is provided by current through a transistor with a VBE of less than 1.0 volts.

16. (Currently Amended) In an electronic device, a method for providing a reference voltage, comprising:

flowing current through an electronic element such that the band-gap voltage of said electronic element provides said reference voltage;

providing a buffer circuit and a band gap voltage reference unit coupled to said buffer circuit ~~enabled to provide low impedance~~; and

adjusting the voltage across said buffer circuit, by use of a voltage pull-up device coupled between said buffer circuit and said band gap voltage reference unit, so that said band-gap reference voltage is maintained, wherein said voltage across said buffer circuit is a VBE of less than 1.0 volts.

17. (Original) A method as described in Claim 16, wherein said electronic device is an integrated circuit device.
18. (Original) A method as described in Claim 16, wherein said buffer circuit is implemented as a transistor circuit.
19. (Original) A method as described in Claim 18, wherein said transistor circuit is connected as an emitter follower.
20. (Original) A method as described in Claim 16, wherein said band-gap reference circuit is enabled for low supply voltage.
21. (Currently Amended) A method as described in Claim 20, wherein said band-gap reference circuit is enabled for said low supply voltage by a voltage pull-up device coupled between said buffer circuit and a band gap reference unit.
22. (Cancelled)
23. (Previously Presented) A method as described in Claim 21, wherein said band gap reference voltage is provided by current through a transistor with a VBE of less than 1.0 volts.